

XV2™

DIMENSION

SPECIFICATION	87200	86200	87300	86300	87400	86400
BLADE WIDTH	8'6"	8'6"	9'6"	9'6"	10'6"	10'6"
APPROX. WEIGHT	972 lbs Does not include vehicle mount (approx. 60 lbs for v-plows). Please refer to eMatch for specific vehicle applications.	972 lbs Does not include vehicle mount (approx. 60 lbs for v-plows). Please refer to eMatch for specific vehicle applications.	1,059 lbs Does not include vehicle mount (approx. 60 lbs for v-plows). Please refer to eMatch for specific vehicle applications.	1,059 lbs Does not include vehicle mount (approx. 60 lbs for v-plows). Please refer to eMatch for specific vehicle applications.	1,322 lb Does not include vehicle mount (approx. 60 lbs for v-plows). Please refer to eMatch for specific vehicle applications.	1,322 lb Does not include vehicle mount (approx. 60 lbs for v-plows). Please refer to eMatch for specific vehicle applications.
PLOWING WIDTH	7'2" - 7'8" Full Angle: 7'5" Scoop: 7'2" Full V: 7'8"	7'2" - 7'8" Full Angle: 7'5" Scoop: 7'2" Full V: 7'8"	8'2" - 8'7" Full Angle: 8'6" Scoop: 8'2" Full V: 8'7"	8'2" - 8'7" Full Angle: 8'6" Scoop: 8'2" Full V: 8'7"	9'7" - 9'11" Full Angle: 9'9" Scoop: 9'7" Full V: 9'11"	9'7" - 9'11" Full Angle: 9'9" Scoop: 9'7" Full V: 9'11"
BLADE HEIGHT	At Center: 31" At End: 38"	At Center: 31" At End: 38"	At Center: 31" At End: 39"	At Center: 31" At End: 39"	At Center: 35" At End: 45"	At Center: 35" At End: 45"
BLADE THICKNESS	14 ga	14 ga	14 ga	14 ga	Powder-Coated: 11 ga Stainless Steel: 12 ga Powder-Coated: 11 ga Stainless Steel: 12 ga	Powder-Coated: 11 ga Stainless Steel: 12 ga
LIFT CYLINDER	1-3/4" x 10"	1-3/4" x 10"	1-3/4" x 10"	1-3/4" x 10"	1-3/4" x 10"	1-3/4" x 10"
ANGLING RAMS	1-3/4" x 11"	1-3/4" x 11"	1-3/4" x 11"	1-3/4" x 11"	2" x 11"	2" x 11"
CUTTING EDGE	3/8" x 6" (Standard)	3/8" x 6" (Standard)	1/2" x 6" (Standard)	1/2" x 6" (Standard)	1/2" x 6" (Standard)	1/2" x 6" (Standard)

CONSTRUCTION

SPECIFICATION	87200	86200	87300	86300	87400	86400
MOLDBOARD OPTIONS	Stainless Steel	Powder-Coated Steel	Stainless Steel	Powder-Coated Steel	Stainless Steel	Powder-Coated Steel
BLADE TYPE	V-Plow	V-Plow	V-Plow	V-Plow	V-Plow	V-Plow
VEHICLE COMPATIBILITY	Truck Class 2 - 6 (under 26,000 lb GVWR) & Tractors	Truck Class 2 - 6 (under 26,000 lb GVWR) & Tractors	Truck Class 2 - 6 (under 26,000 lb GVWR) & Tractors	Truck Class 2 - 6 (under 26,000 lb GVWR) & Tractors	Truck Class 2 - 7 (under 27,500 lb GVWR)	Truck Class 2 - 7 (under 27,500 lb GVWR)
TRIP SPRINGS	4	4	6	6	6	6
RIBS	12	12	12	12	12	12
MOUNT TYPE	Minute Mount® 2	Minute Mount® 2	Minute Mount® 2	Minute Mount® 2	Minute Mount® 2	Minute Mount® 2