

HD2™

DIMENSION

SPECIFICATION	90750	90800	90850	90900
BLADE WIDTH	7'6"	8'	8'6"	9'
APPROX. WEIGHT	709 lbs * Does not include vehicle mount (approx. 60 lbs - 184 lbs for straight blades). Please refer to the eMatch program for specific vehicle applications.	752 lbs * Does not include vehicle mount (approx. 60 lbs - 184 lbs for straight blades). Please refer to the eMatch program for specific vehicle applications.	769 lbs * Does not include vehicle mount (approx. 60 lbs - 184 lbs for straight blades). Please refer to the eMatch program for specific vehicle applications.	789 lbs * Does not include vehicle mount (approx. 60 lbs - 184 lbs for straight blades). Please refer to the eMatch program for specific vehicle applications.
PLOWING WIDTH (FULL ANGLE)	6'9"	7'2"	7'7"	8'1"
BLADE HEIGHT	29"	29"	29"	29"
BLADE THICKNESS	12 ga	12 ga	12 ga	12 ga
LIFT CYLINDER	1-1/2" x 10"	1-1/2" x 10"	1-1/2" x 10"	1-1/2" x 10"
ANGLING RAMS	1-1/2" x 12"	1-1/2" x 12"	1-1/2" x 12"	1-1/2" x 12"
CUTTING EDGE	3/8" x 6" Steel (Standard)	1/2" x 6" Steel (Standard)	1/2" x 6" Steel (Standard)	1/2" x 6" Steel (Standard)

CONSTRUCTION

SPECIFICATION	90750	90800	90850	90900
MOLDBOARD OPTIONS	Powder-Coated Steel	Powder-Coated Steel	Powder-Coated Steel	Powder-Coated Steel
BLADE TYPE	Straight Blade	Straight Blade	Straight Blade	Straight Blade
VEHICLE COMPATIBILITY	Truck Class 2 & 3, Skid-Steers (Under 50 HP) & Tractors Truck Class 2 & 3, Skid-Steers (Under 50 HP) & Tractors	Truck Class 2 & 3, Skid-Steers (Under 50 HP) & Tractors	Truck Class 2 & 3, Skid-Steers (Under 50 HP) & Tractors	Truck Class 2 & 3, Skid-Steers (50 to 70 HP) & Tractors Truck Class 2 & 3, Skid-Steers (50 to 70 HP) & Tractors
TRIP SPRINGS	3	4	4	4
RIBS	10	10	10	10
MOUNT TYPE	Minute Mount® 2	Minute Mount® 2	Minute Mount® 2	Minute Mount® 2