



SPECIFICATION	93800	93900
BLADE WIDTH	8'	9'
MOLDBOARD OPTIONS	Stainless Steel	Stainless Steel
BLADE TYPE	Straight Blade	Straight Blade
VEHICLE COMPATIBILITY	Truck Class 2 & 3, Skid-Steers (Under 50 HP) & Tractors Truck Class 2 & 3, Skid-Steers (Under 50 HP) & Tractors	Truck Class 2 - 5, Skid-Steers (Under 50 HP) & Tractors Truck Class 2 - 5, Skid-Steers (Under 50 HP) & Tractors
APPROX. WEIGHT	861 lb Does not include vehicle mount (approx. 60 lbs - 184 lbs for straight blades). Please refer to the eMatch program for specific vehicle applications.	902 lb Does not include vehicle mount (approx. 60 lbs - 184 lbs for straight blades). Please refer to the eMatch program for specific vehicle applications.
PLOWING WIDTH (FULL ANGLE)	7'2"	8'1"
BLADE HEIGHT	29" Blade height shown is for the 55° attack angle. The 65° attack angle blade height is 28.5" and the 75° attack angle blade height is 27.0".	29" Blade height shown is for the 55° attack angle. The 65° attack angle blade height is 28.5" and the 75° attack angle blade height is 27.0".
BLADE THICKNESS	14 ga	14 ga
TRIP SPRINGS	4	4
RIBS	8	8
LIFT CYLINDER	1-1/2" x 10"	1-1/2" x 10"
ANGLING RAMS	1-1/2" x 12"	1-1/2" x 12"
CUTTING EDGE	1/2" x 6" Steel (Standard)	1/2" x 6" Steel (Standard)
MOUNT TYPE	Minute Mount® 2	Minute Mount® 2