SPECIFICATIONS · IMPERIAL

# XtremeV™

## DIMENSION

| SPECIFICATION | 44785-2 | 44685-2 | 44795-2 | 44695-2 |
|---|---|---|---|---|
| **BLADE WIDTH** | 8'6" | 8'6" | 9'6" | 9'6" |
| **APPROX. WEIGHT** | 876 lbs<br>Does not include vehicle mount (approx. 60 lbs for v-plows). Please refer to the eMatch program for specific vehicle applications. | 876 lbs<br>Does not include vehicle mount (approx. 60 lbs for v-plows). Please refer to the eMatch program for specific vehicle applications. | 984 lbs<br>Does not include vehicle mount (approx. 60 lbs for v-plows). Please refer to the eMatch program for specific vehicle applications. | 984 lbs<br>Does not include vehicle mount (approx. 60 lbs for v-plows). Please refer to the eMatch program for specific vehicle applications. |
| **PLOWING WIDTH (FULL ANGLE)** | 7'1" - 7'7"<br>Full Angle: 7'5" Scoop: 7'1" Full V: 7'7" | 7'1" - 7'7"<br>Full Angle: 7'5" Scoop: 7'1" Full V: 7'7" | 7'11" - 8'7"<br>Full Angle: 8'3" Scoop: 7'11" Full V: 8'7" | 7'11" - 8'7"<br>Full Angle: 8'3" Scoop: 7'11" Full V: 8'7" |
| **BLADE HEIGHT** | At Center: 29"<br>At End: 31" | At Center: 29"<br>At End: 31" | At Center: 31"<br>At End: 33" | At Center: 31"<br>At End: 33" |
| **BLADE GAUGE** | 14 ga | 14 ga | 14 ga | 14 ga |
| **LIFT CYLINDER** | 1-1/2" x 10" | 1-1/2" x 10" | 1-1/2" x 10" | 1-1/2" x 10" |
| **ANGLING RAMS** | 1-3/4" x 11" | 1-3/4" x 11" | 1-3/4" x 11" | 1-3/4" x 11" |
| **CUTTING EDGE** | 3/8" x 6" (Standard) | 3/8" x 6" (Standard) | 1/2" x 6" (Standard) | 1/2" x 6" (Standard) |

## CONSTRUCTION

| SPECIFICATION | 44785-2 | 44685-2 | 44795-2 | 44695-2 |
|---|---|---|---|---|
| **MOLDBOARD OPTIONS** | Stainless Steel | Powder-Coated Steel | Stainless Steel | Powder-Coated Steel |
| **BLADE TYPE** | V-Plow | V-Plow | V-Plow | V-Plow |
| **VEHICLE COMPATIBILITY** | Truck Class 2-3 & Tractors | Truck Class 2-3 & Tractors | Truck Class 2-3 & Tractors | Truck Class 2-3 & Tractors |
| **TRIP SPRINGS** | 4 | 4 | 6 | 6 |
| **RIBS** | 12 | 12 | 12 | 12 |
| **MOUNT TYPE** | Minute Mount® 2 | Minute Mount® 2 | Minute Mount® 2 | Minute Mount® 2 |