SPECIFICATIONS · IMPERIAL

XtremeV™

DIMENSION

SPECIFICATION	44785-2	44685-2	44795-2	44695-2
BLADE WIDTH	8'6"	8'6"	9'6"	9'6"
APPROX. WEIGHT	876 lbs Does not include vehicle mount (approx. 60 lbs for v-plows). Please refer to the eMatch program for specific vehicle applications.	876 lbs Does not include vehicle mount (approx. 60 lbs for v-plows). Please refer to the eMatch program for specific vehicle applications.	984 lbs Does not include vehicle mount (approx. 60 lbs for v-plows). Please refer to the eMatch program for specific vehicle applications.	984 lbs Does not include vehicle mount (approx. 60 lbs for v-plows). Please refer to the eMatch program for specific vehicle applications.
PLOWING WIDTH (FULL ANGLE)	7'1" - 7'7" Full Angle: 7'5" Scoop: 7'1" Full V: 7'7"	7'1" - 7'7" Full Angle: 7'5" Scoop: 7'1" Full V: 7'7"	7'11" - 8'7" Full Angle: 8'3" Scoop: 7'11" Full V: 8'7"	7'11" - 8'7" Full Angle: 8'3" Scoop: 7'11" Full V: 8'7"
BLADE HEIGHT	At Center: 29" At End: 31"	At Center: 29" At End: 31"	At Center: 31" At End: 33"	At Center: 31" At End: 33"
BLADE GAUGE	14 ga	14 ga	14 ga	14 ga
LIFT CYLINDER	1-1/2" x 10"	1-1/2" x 10"	1-1/2" x 10"	1-1/2" x 10"
ANGLING RAMS	1-3/4" x 11"	1-3/4" x 11"	1-3/4" x 11"	1-3/4" x 11"
CUTTING EDGE	3/8" x 6" (Standard)	3/8" x 6" (Standard)	1/2" x 6" (Standard)	1/2" x 6" (Standard)

CONSTRUCTION

SPECIFICATION	44785-2	44685-2	44795-2	44695-2
MOLDBOARD OPTIONS	Stainless Steel	Powder-Coated Steel	Stainless Steel	Powder-Coated Steel
BLADE TYPE	V-Plow	V-Plow	V-Plow	V-Plow
VEHICLE COMPATIBILITY	Truck Class 2-3 & Tractors	Truck Class 2-3 & Tractors	Truck Class 2-3 & Tractors	Truck Class 2-3 & Tractors
TRIP SPRINGS	4	4	6	6
RIBS	12	12	12	12
MOUNT TYPE	Minute Mount® 2	Minute Mount® 2	Minute Mount® 2	Minute Mount® 2