



DIMENSION

SPECIFICATION	95160	95150
BLADE WIDTH	7'6"	7'6"
APPROX. WEIGHT	550 lbs * Does not include vehicle mount (approx. 60 lbs for v-plows). Please refer to the eMatch program for specific vehicle applications.	510 lbs * Does not include vehicle mount (approx. 60 lbs for v-plows). Please refer to the eMatch program for specific vehicle applications.
PLOWING WIDTH	Full Angle: 6'7" Scoop: 6'5" Full V: 6'9"	Full Angle: 6'7" Scoop: 6'5" Full V: 6'9"
BLADE HEIGHT	At Center: 27" At End: 33"	At Center: 27" At End: 33"
BLADE THICKNESS	14 ga	14 ga
LIFT CYLINDER	1-1/4" x 8.63"	1-1/4" x 8.63"
ANGLING RAMS	1-1/2" x 12"	1-1/2" x 12"
CUTTING EDGE	3/8" x 6" (Standard)	3/8" x 6" (Standard)

CONSTRUCTION

SPECIFICATION	95160	95150
MOLDBOARD OPTIONS	Stainless Steel	Powder-Coated Steel
BLADE TYPE	V-Plow	V-Plow
VEHICLE COMPATIBILITY	Half-Ton Trucks & Series 3 Tractors	Half-Ton Trucks & Series 3 Tractors
TRIP SPRINGS	2	2
RIBS	6 Vertical 2 Horizontal	6 Vertical
MOUNT TYPE	Minute Mount® 2	Minute Mount® 2