

SD Series

| Imperial | 6'9" | 7'6" |
|---------------------------------|-------------------------|-------------------------|
| Moldboard Options | Powder-Coated Steel | Powder-Coated Steel |
| Blade Type | Straight Blade | Straight Blade |
| Vehicle Compatibility | Truck Class 2 & 3 | Truck Class 2 & 3 |
| Approx. Weight* (Without Mount) | 501 lbs | 517 lbs |
| Plowing Width (Full Angle) | 6'1" | 6'9" |
| Blade Width | 6'9" | 7'6" |
| Blade Height | 26" | 26" |
| Blade Thickness | 14 ga | 14 ga |
| Trip Springs | 2 | 2 |
| Ribs | 8 | 8 |
| Lift Cylinder | 1½" x 6" | 1½" x 6" |
| Angling Rams | 1½" x 10" | 1½" x 10" |
| Cutting Edge | 1" x 6" Poly (Standard) | 1" x 6" Poly (Standard) |
| Mount Type | Minute Mount® 2 | Minute Mount® 2 |

| Metric | 6'9" | 7'6" |
|---------------------------------|------------------------------------|------------------------------------|
| Models | 6'9" | 7'6" |
| Moldboard Options | Powder-Coated Steel | Powder-Coated Steel |
| Blade Type | Straight Blade | Straight Blade |
| Vehicle Compatibility | Truck Class 2 & 3 | Truck Class 2 & 3 |
| Approx. Weight* (Without Mount) | 227 kg | 234 kg |
| Plowing Width (Full Angle) | 1.85 m | 2.06 m |
| Blade Width | 2.06 m | 2.29 m |
| Blade Height | 66.04 cm | 66.04 cm |
| Blade Thickness | 14 ga | 14 ga |
| Trip Springs | 2 | 2 |
| Ribs | 8 | 8 |
| Lift Cylinder | 3.81 cm x 15.24 cm | 3.81 cm x 15.24 cm |
| Angling Rams | 3.81 cm x 25.40 cm | 3.81 cm x 25.40 cm |
| Cutting Edge | 2.54 cm x 15.24 cm Poly (Standard) | 2.54 cm x 15.24 cm Poly (Standard) |
| Mount Type | Minute Mount® 2 | Minute Mount® 2 |

**Does not include vehicle mount (approx. 60 lbs - 184 lbs for straight blades). Please refer to the eMatch program for specific vehicle applications.*