



STORM BOXX TRACE

Imperial	8'	10'	8' (36"H)	10' (36"H)	12'	14' (Coming Soon!)	16' (Coming Soon!)
Moldboard Options	Steel	Steel	Steel	Steel	Steel	Steel	Steel
Blade Width	8'	10'	8'	10'	12'	14'	16'
Blade Height	30"	30"	36"	36"	42"	42"	42"
Side Plate Width	56"	56"	56"	56"	56"	56"	56"
Side Plate Height	30"	36"	36"	42"	42"	42"	42"
Moldboard Radius	27"	27"	27"	27"	46"	46"	46"
Approx. Snow Capacity	75 cu ft	94 cu ft	108 cu ft	135 cu ft	219 cu ft	TBD	TBD
Machine Application	Skid-Steer	Skid-Steer	Skid-Steer / Tractor / Wheel Loader	Skid-Steer / Tractor / Wheel Loader	Skid-Steer / Tractor / Wheel Loader	Wheel Loader	Wheel Loader
Approx. Weight*	2,127 lb	2,249 lb	2,221 lb	2,377 lb	2,644 lb	2,907 lb	3,170 lb
Cutting Edge Technology	TRACE -- Terrain Response Advanced Cutting Edge	TRACE -- Terrain Response Advanced Cutting Edge	TRACE -- Terrain Response Advanced Cutting Edge	TRACE -- Terrain Response Advanced Cutting Edge	TRACE -- Terrain Response Advanced Cutting Edge	TRACE -- Terrain Response Advanced Cutting Edge	TRACE -- Terrain Response Advanced Cutting Edge
Cutting Edge Material	High-Carbon Steel With Carbide Inserts	High-Carbon Steel With Carbide Inserts	High-Carbon Steel With Carbide Inserts	High-Carbon Steel With Carbide Inserts	High-Carbon Steel With Carbide Inserts	High-Carbon Steel With Carbide Inserts	High-Carbon Steel With Carbide Inserts
Mount Type	Skid-Steer	Skid-Steer	Skid-Steer / Coupler	Skid-Steer / Coupler	Coupler	Coupler	Coupler
Skid-Steer Horsepower Compatibility	30-50 hp	30-50 hp	--	--	--	--	--
Wheel Loader & Backhoe Horsepower Compatibility	--	--	50-75 hp	50-75 hp	100-125 hp	100-125 hp	100-125 hp
Tractor Horsepower Compatibility	--	--	50-100 hp	50-100 hp	75-150 hp	75-150 hp	75-150 hp

Metric	8'	10'	8' (36"H)	10' (36"H)	12'	14' (Coming Soon!)	16' (Coming Soon!)
Models	8'	10'	8' (36"H)	10' (36"H)	12'	14' (Coming Soon!)	16' (Coming Soon!)
Moldboard Options	Steel	Steel	Steel	Steel	Steel	Steel	Steel



STORM BOXX TRACE

Blade Width	2.44 m	3.05 m	2.44 m	3.05 m	3.66 m	4.27 m	4.88 m
Blade Height	76.2 cm	76.2 cm	91.44 cm	91.44 cm	106.68 cm	106.68 cm	106.68 cm
Side Plate Width	142.24 cm	142.24 cm	142.24 cm	142.24 cm	142.24 cm	142.24 cm	142.24 cm
Side Plate Height	76.2 cm	91.44 cm	91.44 cm	106.68 cm	106.68 cm	106.68 cm	106.68 cm
Moldboard Radius	68.58 cm	68.58 cm	68.58 cm	68.58 cm	116.84 cm	116.84 cm	116.84 cm
Approx. Snow Capacity	2.14 cu m	2.68 cu m	3.06 cu m	3.82 cu m	6.19 cu m	TBD	TBD
Machine Application	Skid-Steer	Skid-Steer	Skid-Steer / Tractor / Wheel Loader	Skid-Steer / Tractor / Wheel Loader	Skid-Steer / Tractor / Wheel Loader	Wheel Loader	Wheel Loader
Approx. Weight*	964.63 kg	1,019.95 kg	1,007.26 kg	1,078.00 kg	1,199.09 kg	1,318.37 kg	1,437.64 kg
Cutting Edge Technology	TRACE -- Terrain Response Advanced Cutting Edge	TRACE -- Terrain Response Advanced Cutting Edge	TRACE -- Terrain Response Advanced Cutting Edge	TRACE -- Terrain Response Advanced Cutting Edge	TRACE -- Terrain Response Advanced Cutting Edge	TRACE -- Terrain Response Advanced Cutting Edge	TRACE -- Terrain Response Advanced Cutting Edge
Cutting Edge Material	High-Carbon Steel With Carbide Inserts	High-Carbon Steel With Carbide Inserts	High-Carbon Steel With Carbide Inserts	High-Carbon Steel With Carbide Inserts	High-Carbon Steel With Carbide Inserts	High-Carbon Steel With Carbide Inserts	High-Carbon Steel With Carbide Inserts
Mount Type	Skid-Steer	Skid-Steer	Skid-Steer / Coupler	Skid-Steer / Coupler	Coupler	Coupler	Coupler
Skid-Steer Horsepower Compatibility	30-50 hp	30-50 hp	--	--	--	--	--
Wheel Loader & Backhoe Horsepower Compatibility	--	--	50-75 hp	50-75 hp	100-125 hp	100-125 hp	100-125 hp
Tractor Horsepower Compatibility	--	--	50-100 hp	50-100 hp	75-150 hp	75-150 hp	75-150 hp

*Does not include vehicle mount weight.