



TRAILCOMMANDER(TM) 250/600

Imperial	250	600
Capacity	2.5 cu ft	6.0 cu ft
Hopper Construction	201 Stainless Steel	201 Stainless Steel
Hopper Dimensions (LxWxH)	12.8" x 36.5" x 17.25"	16.75" x 36.5" x 28"
Dimensions Overall (LxWxH)	17" x 42" x 17 ½"	20" x 42" x 28"
Approx. Weight (Empty)	130 lb	160 lb
Motor	Direct Drive, 12V, Sealed	Direct Drive, 12V, Sealed
Spreading Width	30" to 36"	30" to 36"
Materials*	Salt, Sand, Salt/Sand Mix, Calcium Chloride Pellets & Calcium Flakes	Salt, Sand, Salt/Sand Mix, Calcium Chloride Pellets & Calcium Flakes
Vehicle Application**	UTVs, Compact Tractors & Wheel Loaders	UTVs, Compact Tractors & Wheel Loaders

Metric	250	600
Models	250	600
Capacity	0.07 cu m	0.17 cu m
Hopper Construction	201 Stainless Steel	201 Stainless Steel
Hopper Dimensions (LxWxH)	32.5 cm x 92.7 cm x 43.8 cm	42.54 cm x 92.7 cm x 71.1 cm
Dimensions Overall (LxWxH)	43.2 cm x 106.7 cm x 44.5 cm	50.8 cm x 106.7 cm x 71.1 cm
Approx. Weight (Empty)	58.9 kg	72.6 kg
Motor	Direct Drive, 12V, Sealed	Direct Drive, 12V, Sealed
Spreading Width	76.2 cm to 91.4 cm	76.2 cm to 91.4 cm
Materials*	Salt, Sand, Salt/Sand Mix, Calcium Chloride Pellets & Calcium Flakes	Salt, Sand, Salt/Sand Mix, Calcium Chloride Pellets & Calcium Flakes
Vehicle Application**	UTVs, Compact Tractors & Wheel Loaders	UTVs, Compact Tractors & Wheel Loaders

*When spreading sand, an additional vibrator is required.

**When choosing a spreader, follow weight capacity guidelines for the intended application.