

XV2(TM)

Imperial	87200	86200	87300	86300	87400	86400
Blade Width	8'6"	8'6"	9'6"	9'6"	10'6"	10'6"
Moldboard Options	Stainless Steel	Powder-Coated Steel	Stainless Steel	Powder-Coated Steel	Stainless Steel	Powder-Coated Steel
Blade Type	V-Plow	V-Plow	V-Plow	V-Plow	V-Plow	V-Plow
Vehicle Compatibility	Truck Class 2 - 6 (under 26,000 lb GVWR) & Tractors	Truck Class 2 - 6 (under 26,000 lb GVWR) & Tractors	Truck Class 2 - 6 (under 26,000 lb GVWR) & Tractors	Truck Class 2 - 6 (under 26,000 lb GVWR) & Tractors	Truck Class 2 - 7 (under 27,500 lb GVWR)	Truck Class 2 - 7 (under 27,500 lb GVWR)
Approx. Weight* (Without Mount)	972 lbs	972 lbs	1,059 lbs	1,059 lbs	1,322 lb	1,322 lb
Plowing Width	Full Angle: 7' 5" Scoop: 7' 2" Full V: 7' 8"	Full Angle: 7' 5" Scoop: 7' 2" Full V: 7' 8"	Full Angle: 8' 6" Scoop: 8' 2" Full V: 8' 7"	Full Angle: 8' 6" Scoop: 8' 2" Full V: 8' 7"	Full Angle: 9' 9" Scoop: 9' 7" Full V: 9' 11"	Full Angle: 9' 9" Scoop: 9' 7" Full V: 9' 11"
Blade Height	At Center: 31" At End: 38"	At Center: 31" At End: 38"	At Center: 31" At End: 39"	At Center: 31" At End: 39"	At Center: 35" At End: 45"	At Center: 35" At End: 45"
Blade Thickness	14 ga	14 ga	14 ga	14 ga	Powder-Coated: 11 ga Stainless Steel: 12 ga	Powder-Coated: 11 ga Stainless Steel: 12 ga
Trip Springs	4	4	6	6	6	6
Ribs	12	12	12	12	12	12
Lift Cylinder	1¾" x 10"					
Angling Rams	1¾" x 11"	1¾" x 11"	1¾" x 11"	1¾" x 11"	2" x 11"	2" x 11"
Cutting Edge	3/8 " x 6" (Standard)	3/8 " x 6" (Standard)	½" x 6" (Standard)	½" x 6" (Standard)	½" x 6" (Standard)	½" x 6" (Standard)
Mount Type	Minute Mount® 2					

Metric	87200	86200	87300	86300	87400	86400
Models	87200	86200	87300	86300	87400	86400
Blade Width	2.59 m	2.59 m	2.90 m	2.90 m	3.20 m	3.20 m
Moldboard Options	Stainless Steel	Powder-Coated Steel	Stainless Steel	Powder-Coated Steel	Stainless Steel	Powder-Coated Steel
Blade Type	V-Plow	V-Plow	V-Plow	V-Plow	V-Plow	V-Plow
Vehicle Compatibility	Truck Class 2 - 6 (under 26,000 lb GVWR) & Tractors	Truck Class 2 - 6 (under 26,000 lb GVWR) & Tractors	Truck Class 2 - 6 (under 26,000 lb GVWR) & Tractors	Truck Class 2 - 6 (under 26,000 lb GVWR) & Tractors	Truck Class 2 - 7 (under 27,500 lb GVWR)	Truck Class 2 - 7 (under 27,500 lb GVWR)
Approx. Weight* (Without Mount)	440 kg	440 kg	480 kg	480 kg	599 kg	599 kg
Plowing Width	Full Angle: 2.26 m Scoop: 2.18 m Full V: 2.34 m	Full Angle: 2.26 m Scoop: 2.18 m Full V: 2.34 m	Full Angle: 2.59 m Scoop: 2.49 m Full V: 2.62 m	Full Angle: 2.59 m Scoop: 2.49 m Full V: 2.62 m	Full Angle: 2.97 m Scoop: 2.92 m Full V: 3.02 m	Full Angle: 2.97 m Scoop: 2.92 m Full V: 3.02 m

XV2(TM)

Blade Height	At Center: 78.74 cm At End: 96.52 cm	At Center: 78.74 cm At End: 96.52 cm	At Center: 78.74 cm At End: 99.06 cm	At Center: 78.74 cm At End: 99.06 cm	At Center: 88.90 cm At End: 114.30 cm	At Center: 88.90 cm At End: 114.30 cm
Blade Thickness	14 ga	14 ga	14 ga	14 ga	Powder-Coated: 11 ga Stainless Steel: 12 ga	Powder-Coated: 11 ga Stainless Steel: 12 ga
Trip Springs	4	4	6	6	6	6
Ribs	12	12	12	12	12	12
Lift Cylinder	4.45 cm x 25.40 cm	4.45 cm x 25.40 cm				
Angling Rams	4.45 cm x 27.94 cm	5.08 cm x 27.94 cm	5.08 cm x 27.94 cm			
Cutting Edge	0.95 cm x 15.24 cm (Standard)	0.95 cm x 15.24 cm (Standard)	1.27 cm x 15.24 cm (Standard)	1.27 cm x 15.24 cm (Standard)	1.27 cm x 15.24 cm (Standard)	1.27 cm x 15.24 cm (Standard)
Mount Type	Minute Mount® 2	Minute Mount® 2				

* Does not include vehicle mount (approx. 60 lbs for v-plows). Please refer to eMatch for specific vehicle applications.