Imperial	87200	86200	87300	86300	87400	86400
Blade Width	8'6"	8'6"	9'6"	9'6"	10'6"	10'6"
Moldboard	Stainless Steel	Powder-Coated	Stainless Steel	Powder-Coated	Stainless Steel	Powder-Coated
Options		Steel		Steel		Steel
Blade Type	V-Plow	V-Plow	V-Plow	V-Plow	V-Plow	V-Plow
Vehicle	Truck Class 2 - 6	Truck Class 2 - 7	Truck Class 2 - 7			
Compatibility	(under 26,000 lb	(under 26,000 lb	(under 26,000 lb	(under 26,000 lb	(under 27,500 lb	(under 27,500 lb
	GVWR) &					
	Tractors	Tractors	Tractors	Tractors	Tractors	Tractors
Approx. Weight*	972 lbs	972 lbs	1,059 lbs	1,059 lbs	1,322 lb	1,322 lb
(Without Mount)						
Plowing Width	Full Angle: 7' 5"	Full Angle: 7' 5"	Full Angle: 8' 6"	Full Angle: 8' 6"	Full Angle: 9' 9"	Full Angle: 9' 9"
	Scoop: 7' 2"	Scoop: 7' 2"	Scoop: 8' 2"	Scoop: 8' 2"	Scoop: 9' 7"	Scoop: 9' 7"
	Full V: 7' 8"	Full V: 7' 8"	Full V: 8' 7"	Full V: 8' 7"	Full V: 9' 11"	Full V: 9' 11"
Blade Height	At Center: 31"	At Center: 31"	At Center: 31"	At Center: 31"	At Center: 35"	At Center: 35"
	At End: 38"	At End: 38"	At End: 39"	At End: 39"	At End: 45"	At End: 45"
Blade Thickness	14 ga	14 ga	14 ga	14 ga	Powder-Coated:	Powder-Coated:
					11 ga	11 ga
					Stainless Steel:	Stainless Steel:
					12 ga	12 ga
Trip Springs	4	4	6	6	6	6
Ribs	12	12	12	12	12	12
Lift Cylinder	1¾" x 10"					
Angling Rams	1¾" x 11"	1¾" x 11"	1¾" x 11"	1¾" x 11"	2" x 11"	2" x 11"
Cutting Edge	3/8 " x 6"	3/8 " x 6"	½" x 6"	½" x 6"	½" x 6"	½" x 6"
	(Standard)	(Standard)	(Standard)	(Standard)	(Standard)	(Standard)
Mount Type	Minute Mount® 2					

Metric	87200	86200	87300	86300	87400	86400
Models	87200	86200	87300	86300	87400	86400
Blade Width	2.59 m	2.59 m	2.90 m	2.90 m	3.20 m	3.20 m
Moldboard	Stainless Steel	Powder-Coated	Stainless Steel	Powder-Coated	Stainless Steel	Powder-Coated
Options		Steel		Steel		Steel
Blade Type	V-Plow	V-Plow	V-Plow	V-Plow	V-Plow	V-Plow
Vehicle	Truck Class 2 - 6	Truck Class 2 - 7	Truck Class 2 - 7			
Compatibility	(under 26,000 lb	(under 26,000 lb	(under 26,000 lb	(under 26,000 lb	(under 27,500 lb	(under 27,500 lb
	GVWR) &					
	Tractors	Tractors	Tractors	Tractors	Tractors	Tractors
Approx. Weight*	440 kg	440 kg	480 kg	480 kg	599 kg	599 kg
(Without Mount)						
Plowing Width	Full Angle: 2.26	Full Angle: 2.26	Full Angle: 2.59	Full Angle: 2.59	Full Angle: 2.97	Full Angle: 2.97
	m	m	m	m	m	m
	Scoop: 2.18 m	Scoop: 2.18 m	Scoop: 2.49 m	Scoop: 2.49 m	Scoop: 2.92 m	Scoop: 2.92 m
	Full V: 2.34 m	Full V: 2.34 m	Full V: 2.62 m	Full V: 2.62 m	Full V: 3.02 m	Full V: 3.02 m

## XV2(TM)

Γ=	T	1	1	1	1	1
Blade Height	At Center: 78.74	At Center: 78.74	At Center: 78.74	At Center: 78.74	At Center: 88.90	At Center: 88.90
	cm	cm	cm	cm	cm	cm
	At End: 96.52 cm	At End: 96.52 cm	At End: 99.06 cm	At End: 99.06 cm	At End: 114.30	At End: 114.30
					cm	cm
Blade Thickness	14 ga	14 ga	14 ga	14 ga	Powder-Coated:	Powder-Coated:
					11 ga	11 ga
					Stainless Steel:	Stainless Steel:
					12 ga	12 ga
Trip Springs	4	4	6	6	6	6
Ribs	12	12	12	12	12	12
Lift Cylinder	4.45 cm x 25.40					
	cm	cm	cm	cm	cm	cm
Angling Rams	4.45 cm x 27.94	5.08 cm x 27.94	5.08 cm x 27.94			
	cm	cm	cm	cm	cm	cm
Cutting Edge	0.95 cm x 15.24	0.95 cm x 15.24	1.27 cm x 15.24			
	cm (Standard)					
Mount Type	Minute Mount® 2					

<sup>\*</sup> Does not include vehicle mount (approx. 60 lbs for v-plows). Please refer to eMatch for specific vehicle applications.