



XV2(TM)

Imperial	8' 6" PC or SS	9' 6" PC or SS	10' 6" PC or SS
Blade Width	8' 6"	9' 6"	10' 6"
Blade Height	31" at Center 38" at End	31" at Center 39" at End	35" at Center 45" at End
Blade Gauge	14	14	11 PC 12 SS
Trip Springs	4	6	6
Ribs	12	12	12
Lift Cylinder	1 ¾" x 10"	1 ¾" x 10"	1 ¾" x 10"
Angling Rams	1 ¾" x 11"	1 ¾" x 11"	2" x 11"
Plowing Width	7' 5" Full Angle 7' 2" Scoop 7' 8" Full V	8' 6" Full Angle 8' 2" Scoop 8' 7" Full V	9' 9" Full Angle 9' 7" Scoop 9' 11" Full V
Approx. Weight*	957 lb	1,044 lb	1,222 lb
Cutting Edge	3/8" x 6" ½" x 6"***	½" x 6"	½" x 6"
Mount Type	Minute Mount® 2	Minute Mount® 2	Minute Mount® 2

Metric	8' 6" PC or SS	9' 6" PC or SS	10' 6" PC or SS
Models	8' 6" PC or SS	9' 6" PC or SS	10' 6" PC or SS
Blade Width	2.59 m	2.90 m	3.20 m
Blade Height	78.74 cm at Center 96.52 cm at End	78.74 cm at Center 99.06 cm at End	88.90 cm at Center 114.30 cm at End
Blade Gauge	1.98 mm	1.98 mm	3.05 mm PC 2.66 mm SS
Trip Springs	4	6	6
Ribs	12	12	12
Lift Cylinder	4.44 cm x 25.40 cm	4.44 cm x 25.40 cm	4.44 cm x 25.40 cm
Angling Rams	4.44 cm x 27.94 cm	4.44 cm x 27.94 cm	5.08 cm x 27.94 cm
Plowing Width	2.26 m Full Angle 2.18 m Scoop 2.34 m Full V	2.59 m Full Angle 2.49 m Scoop 2.62 m Full V	2.97 m Full Angle 2.92 m Scoop 3.02 m Full V
Approx. Weight*	434 kg	473 kg	554 kg
Cutting Edge	0.95 cm x 15.24 cm 1.27 cm x 15.24 cm**	1.27 cm x 15.24 cm	1.27 cm x 15.24 cm
Mount Type	Minute Mount® 2	Minute Mount® 2	Minute Mount® 2

PC = Powder Coated Steel

SS = Stainless Steel

*Does not include vehicle mount. Please refer to the eMatch program for specific vehicle applications.

** Optional accessory