



HD2(TM)

Imperial	7' 6"	8'	8' 6"	9'
Blade Width	7' 6"	8'	8' 6"	9'
Blade Height	29"	29"	29"	29"
Blade Gauge	12	12	12	12
Trip Springs	3	4	4	4
Ribs	10	10	10	10
Lift Cylinder	1 ½" x 10"	1 ½" x 10"	1 ½" x 10"	1 ½" x 10"
Angling Rams	1 ½" x 12"	1 ½" x 12"	1 ½" x 12"	1 ½" x 12"
Plowing Width (Full Angle)	6' 9"	7' 2"	7' 7"	8' 1"
Approx. Weight*	684 lb	734 lb	750 lb	770 lb
Cutting Edge	3/8 " x 6" Steel	½" x 6" Steel	½" x 6" Steel	½" x 6" Steel
Mount Type	Minute Mount® 2	Minute Mount® 2	Minute Mount® 2	Minute Mount® 2

Metric	7' 6"	8'	8' 6"	9'
Models	7' 6"	8'	8' 6"	9'
Blade Width	2.29 m	2.44 m	2.59 m	2.74 m
Blade Height	73.66 cm	73.66 cm	73.66 cm	73.66 cm
Blade Gauge	2.66 mm	2.66 mm	2.66 mm	2.66 mm
Trip Springs	3	4	4	4
Ribs	10	10	10	10
Lift Cylinder	3.81 cm x 25.40 cm	3.81 cm x 25.40 cm	3.81 cm x 25.40 cm	3.81 cm x 25.40 cm
Angling Rams	3.81 cm x 30.48 cm	3.81 cm x 30.48 cm	3.81 cm x 30.48 cm	3.81 cm x 30.48 cm
Plowing Width (Full Angle)	2.05 m	2.19 m	2.32 m	2.46 m
Approx. Weight*	310 kg	332 kg	340 kg	349 kg
Cutting Edge	0.95 cm x 15.24 cm	1.27 cm x 15.24 cm	1.27 cm x 15.24 cm	1.27 cm x 15.24 cm
Mount Type	Minute Mount® 2	Minute Mount® 2	Minute Mount® 2	Minute Mount® 2

*Does not include vehicle mount. Please refer to the eMatch program for specific vehicle applications.