

STORM BOXX HX (TRACE)

Imperial	32708-3	32308-2	32710-3	32310-2	32614-3	32312-3	32594-3	32314-3	32596-3	32316-3
Blade Size	8' x 30"	8' x 36"	10' x 30"	10' x 36"	12' x 30"	12' x 42"	14' x 30"	14' x 42"	16' x 30"	16' x 42"
Moldboard Options	Powder-Coated Steel	Powder-Coated Steel	Powder-Coated Steel	Powder-Coated Steel	Powder-Coated Steel	Powder-Coated Steel	Powder-Coated Steel	Powder-Coated Steel	Powder-Coated Steel	Powder-Coated Steel
Blade Type	Pusher	Pusher	Pusher	Pusher	Pusher	Pusher	Pusher	Pusher	Pusher	Pusher
Vehicle Compatibility	Skid-Steer	Tractor / Wheel Loader	Skid-Steer	Tractor / Wheel Loader	Compact Wheel Loaders, Wheel Loaders (9,000-25,000 lb), Skid Steers (9,000 lb+), Tractors	Tractor / Wheel Loader	Compact Wheel Loaders, Wheel Loaders (9,000-25,000 lb), Skid Steers (9,000 lb+), Tractors	Wheel Loader	Compact Wheel Loaders, Wheel Loaders (9,000-25,000 lb), Skid Steers (9,000 lb+), Tractors	Wheel Loader
Approx. Weight* (Without Mount)	2,533 lb	2,628 lb	2,770 lb	2,822 lb	2,950 lb	3,197 lb	3,317 lb	3,666 lb	3,551 lb	3,855 lb
Application Weight (Max Operating Weight)	8,000 lb	10,000 lb	9,000 lb	12,000 lb	25,000 lb	25,000 lb	25,000 lb	30,000 lb	25,000 lb	35,000 lb
Horsepower Compatibility	45+ hp (Skid-Steer)	40+ hp (Tractor) & 60+ hp (Wheel Loader & Backhoe)	60+ hp (Skid-Steer) & 60+ hp (Wheel Loader & Backhoe)	50+ hp (Tractor) & 60+ hp (Wheel Loader & Backhoe)	40+ hp (Tractor) 60+ hp (Wheel Loader)	100+ hp (Wheel Loader & Backhoe)	40+ hp (Tractor) 60+ hp (Wheel Loader)	140+ hp (Wheel Loader & Backhoe)	40+ hp (Tractor) 60+ hp (Wheel Loader)	140+ hp (Wheel Loader & Backhoe)
Blade Width	8'	8'	10'	10'	12'	12'	14'	14'	16'	16'
Blade Height	30"	36"	30"	36"	30"	42"	30"	42"	30"	42"
Side Plate Width	36"	36"	36"	36"	36"	36"	36"	36"	36"	36"
Side Plate Height	30"	36"	30"	36"	30"	42"	42"	42"	42"	42"
Moldboard Radius	27"	27"	27"	27"	27"	46"	27"	46"	27"	46"

STORM BOXX HX (TRACE)

Approx. Snow Capacity	75 cu ft	108 cu ft	94 cu ft	135 cu ft	113 cu ft	219 cu ft	132 cu ft	250 cu ft	151 cu ft	280 cu ft
Cutting Edge Technology	TRACE -- Terrain Response Advanced Cutting Edge									
Cutting Edge Material	High-Carb on Steel With Carbide Inserts									
Mount Type	Skid-Steer Attach Plate	Skid-Steer Attach Plate / Coupler	Skid-Steer Attach Plate / Coupler	Skid-Steer Attach Plate / Coupler	Coupler	Coupler	Coupler	Coupler	Coupler	Coupler

Metric	32708-3	32308-2	32710-3	32310-2	32614-3	32312-3	32594-3	32314-3	32596-3	32316-3
Models	32708-3	32308-2	32710-3	32310-2	32614-3	32312-3	32594-3	32314-3	32596-3	32316-3
Blade Size	8' x 30"	8' x 36"	10' x 30"	10' x 36"	12' x 30"	12' x 42"	14' x 30"	14' x 42"	16' x 30"	16' x 42"
Moldboard Options	Powder-Coated Steel	Powder-Coated Steel	Powder-Coated Steel	Powder-Coated Steel	Powder-Coated Steel	Powder-Coated Steel	Powder-Coated Steel	Powder-Coated Steel	Powder-Coated Steel	Powder-Coated Steel
Blade Type	Pusher	Pusher	Pusher	Pusher	Pusher	Pusher	Pusher	Pusher	Pusher	Pusher
Vehicle Compatibility	Skid-Steer	Tractor / Wheel Loader	Skid-Steer	Tractor / Wheel Loader	Compact Wheel Loaders, Wheel Loaders (9,000-25,000 lb), Skid Steers (9,000 lb+), Tractors	Tractor / Wheel Loader	Compact Wheel Loaders, Wheel Loaders (9,000-25,000 lb), Skid Steers (9,000 lb+), Tractors	Wheel Loader	Compact Wheel Loaders, Wheel Loaders (9,000-25,000 lb), Skid Steers (9,000 lb+), Tractors	Wheel Loader
Approx. Weight* (Without Mount)	1,148.9 kg	1,192.0 kg	1,256.5 kg	1,280.1 kg	1,340.9 kg	1,450.1 kg	1,507.7 kg	1,662.9 kg	1,614.1 kg	1,748.6 kg

STORM BOXX HX (TRACE)

Application Weight (Max Operating Weight)	3,628.7 kg	4,535.9 kg	4,082.3 kg	5,443.1 kg	11,339.8 kg	11,339.8 kg	11,339.8 kg	13,607.8 kg	11,339.8 kg	15,875.7 kg
Horsepower Compatibility	45+ hp (Skid-Steer & 60+ hp (Wheel Loader & Backhoe)	40+ hp (Tractor) & 60+ hp (Wheel Loader & Backhoe)	60+ hp (Skid-Steer & 60+ hp (Wheel Loader & Backhoe)	50+ hp (Tractor) & 60+ hp (Wheel Loader & Backhoe)	40+ hp (Tractor) & 60+ hp (Wheel Loader)	100+ hp (Wheel Loader & Backhoe)	40+ hp (Tractor) & 60+ hp (Wheel Loader)	140+ hp (Wheel Loader & Backhoe)	40+ hp (Tractor) & 60+ hp (Wheel Loader)	140+ hp (Wheel Loader & Backhoe)
Blade Width	2.44 m	2.44 m	3.05 m	3.05 m	3.66 m	3.66 m	4.27 m	4.27 m	4.88 m	4.88 m
Blade Height	76.2 cm	91.44 cm	76.2 cm	91.44 cm	76.20 cm	106.68 cm	76.20 cm	106.68 cm	76.20 cm	106.68 cm
Side Plate Width	91.44 cm	91.44 cm	91.44 cm	91.44 cm	91.44 cm	91.44 cm	91.44 cm	91.44 cm	91.44 cm	91.44 cm
Side Plate Height	76.2 cm	91.44 cm	76.2 cm	91.44 cm	76.20 cm	106.68 cm	106.68 cm	106.68 cm	106.68 cm	106.68 cm
Moldboard Radius	68.58 cm	68.58 cm	68.58 cm	68.58 cm	68.58 cm	116.84 cm	68.58 cm	116.84 cm	68.58 cm	116.84 cm
Approx. Snow Capacity	2.12 cu m	3.06 cu m	2.66 cu m	3.82 cu m	3.20 cu m	6.20 cu m	3.73 cu m	7.08 cu m	4.28 cu m	7.96 cu m
Cutting Edge Technology	TRACE -- Terrain Response Advanced Cutting Edge	TRACE -- Terrain Response Advanced Cutting Edge	TRACE -- Terrain Response Advanced Cutting Edge	TRACE -- Terrain Response Advanced Cutting Edge	TRACE -- Terrain Response Advanced Cutting Edge	TRACE -- Terrain Response Advanced Cutting Edge	TRACE -- Terrain Response Advanced Cutting Edge	TRACE -- Terrain Response Advanced Cutting Edge	TRACE -- Terrain Response Advanced Cutting Edge	TRACE -- Terrain Response Advanced Cutting Edge
Cutting Edge Material	High-Carb on Steel With Carbide Inserts	High-Carb on Steel With Carbide Inserts	High-Carb on Steel With Carbide Inserts	High-Carb on Steel With Carbide Inserts	High-Carb on Steel With Carbide Inserts	High-Carb on Steel With Carbide Inserts	High-Carb on Steel With Carbide Inserts	High-Carb on Steel With Carbide Inserts	High-Carb on Steel With Carbide Inserts	High-Carb on Steel With Carbide Inserts
Mount Type	Skid-Steer Attach Plate	Skid-Steer Attach Plate / Coupler	Skid-Steer Attach Plate	Skid-Steer Attach Plate / Coupler	Skid-Steer Attach Plate / Coupler	Coupler	Coupler	Coupler	Coupler	Coupler

*Does not include vehicle mount weight. Please refer to the eMatch program for specific vehicle applications.