

# TEMPEST Poly

<b>Imperial</b>	<b>P150C*</b>	<b>P220C*</b>	<b>P150A*</b>	<b>P220A*</b>
Vehicle Compatibility	3/4- & 1-Ton Pickup Trucks	Pickup or Dump Body/Flatbed Trucks (Over 15,000 lb GVWR)	3/4- & 1-Ton Pickup Trucks	Pickup or Dump Body/Flatbed Trucks (Over 15,000 lb GVWR)
Material Compatibility	Sand, Salt & 50/50 Mix	Sand, Salt & 50/50 Mix	Bulk Rock Salt	Bulk Rock Salt
Capacity (Volume)	1.5 cu yd	2.2 cu yd	1.5 cu yd	2.2 cu yd
Capacity (Weight)	3,240 lb	4,752 lb	3,240 lb	4,752 lb
Spreading Width	Salt: Up to 36' Sand: Up to 24'	Salt: Up to 36' Sand: Up to 24'	Salt: Up to 36'	Salt: Up to 36'
Approx. Weight** (Empty)	723 lb	823 lb	673 lb	793 lb
Hopper Length (A)	96.50"	104.50"	96.50"	104.50"
Length from Cab Side to Second Leg (B)	80"	87"	80"	87"
Overall Hopper Length (C)	108.25"	116.25"	108.25"	116.25"
Reference Diagram (A-C)				
Width of Hopper Opening (D)	63.50"	63.50"	63.50"	63.50"
Height of Hopper w/o Chute (E)	46"	51.50"	46"	51.50"
Reference Diagram (D-E)				

## TEMPEST Poly

Body Side Length	7'	8'	7'	8'
Rec. Bed Length	74"	90"	74"	90"
Material Delivery Dimensions	16" Wide	16" Wide	6" Diameter	6" Diameter
Hopper Construction	Polyethylene Body, Stainless Steel Drive Line	Polyethylene Body, Stainless Steel Drive Line	Polyethylene Body, Stainless Steel Drive Line	Polyethylene Body, Stainless Steel Drive Line
Spinner Size	16" Diameter	16" Diameter	16" Diameter	16" Diameter

<b>Metric</b>	<b>P150C*</b>	<b>P220C*</b>	<b>P150A*</b>	<b>P220A*</b>
Models	P150C*	P220C*	P150A*	P220A*
Vehicle Compatibility	3/4- & 1-Ton Pickup Trucks	Pickup or Dump Body/Flatbed Trucks (Over 15,000 lb GVWR)	3/4- & 1-Ton Pickup Trucks	Pickup or Dump Body/Flatbed Trucks (Over 15,000 lb GVWR)
Material Compatibility	Sand, Salt & 50/50 Mix	Sand, Salt & 50/50 Mix	Bulk Rock Salt	Bulk Rock Salt
Capacity (Volume)	1.15 cu m	1.68 cu m	1.15 cu m	1.68 cu m
Capacity (Weight)	1,469.9 kg	2,155 kg	1,469.9 kg	2,155 kg
Spreading Width	Salt: Up to 10.97 m Sand: 7.32 m	Salt: Up to 10.97 m Sand: 7.32 m	Salt: Up to 10.97 m	Salt: Up to 10.97 m
Approx. Weight** (Empty)	328 kg	373.3 kg	305.3 kg	360 kg
Hopper Length (A)	245.1 cm	265.4 cm	245.1 cm	265.4 cm
Length from Cab Side to Second Leg (B)	203.2 cm	221 cm	203.2 cm	221 cm
Overall Hopper Length (C)	275 cm	295.3 cm	275 cm	295.3 cm
Reference Diagram (A-C)				
Width of Hopper Opening (D)	161.3 cm	161.3 cm	161.3 cm	161.3 cm
Height of Hopper w/o Chute (E)	116.8 cm	130.8 cm	116.8 cm	130.8 cm

# TEMPEST Poly

Reference Diagram (D-E)				
Body Side Length	213.4 cm	243.9 cm	213.4 cm	243.9 cm
Rec. Bed Length	188 cm	228.6 cm	188 cm	228.6 cm
Material Delivery Dimensions	40.6 cm	40.6 cm	15.24 cm Diameter	15.24 cm Diameter
Hopper Construction	Polyethylene Body, Stainless Steel Drive Line	Polyethylene Body, Stainless Steel Drive Line	Polyethylene Body, Stainless Steel Drive Line	Polyethylene Body, Stainless Steel Drive Line
Spinner Size	40.6 cm Diameter	40.6 cm Diameter	40.6 cm Diameter	40.6 cm Diameter

\* C = Pintle Chain Conveyor / A = HELIXX Shaftless Auger \* Material weight equates to approximately 2,160 lb/cu yd or 80 lb/cu ft for 1 bag of rock salt.