



## HDX(TM)

<b>Imperial</b>	<b>93800</b>	<b>93900</b>
Blade Width	8'	9'
Moldboard Options	Stainless Steel	Stainless Steel
Blade Type	Straight Blade	Straight Blade
Vehicle Compatibility	Truck Class 2 & 3, Skid-Steers (Under 50 HP) & Tractors	Truck Class 2 - 5, Skid-Steers (Under 50 HP) & Tractors
Approx. Weight* (Without Mount)	861 lb	902 lb
Plowing Width (Full Angle)	7'2"	8'1"
Blade Height**	29"	29"
Blade Thickness	14 ga	14 ga
Trip Springs	4	4
Ribs	8	8
Lift Cylinder	1½" x 10"	1½" x 10"
Angling Rams	1½" x 12"	1½" x 12"
Cutting Edge	½" x 6" Steel (Standard)	½" x 6" Steel (Standard)
Mount Type	Minute Mount® 2	Minute Mount® 2

<b>Metric</b>	<b>93800</b>	<b>93900</b>
Models	93800	93900
Blade Width	2.44 m	2.74 m
Moldboard Options	Stainless Steel	Stainless Steel
Blade Type	Straight Blade	Straight Blade
Vehicle Compatibility	Truck Class 2 & 3, Skid-Steers (Under 50 HP) & Tractors	Truck Class 2 - 5, Skid-Steers (Under 50 HP) & Tractors
Approx. Weight* (Without Mount)	390 kg	409 kg
Plowing Width (Full Angle)	2.19 m	2.46 m
Blade Height**	73.66 cm	73.66 cm
Blade Thickness	14 ga	14 ga
Trip Springs	4	4
Ribs	8	8
Lift Cylinder	3.81 cm x 25.40 cm	3.81 cm x 25.40 cm
Angling Rams	3.81 cm x 30.48 cm	3.81 cm x 30.48 cm
Cutting Edge	1.27 cm x 15.24 cm (Standard)	1.27 cm x 15.24 cm (Standard)
Mount Type	Minute Mount® 2	Minute Mount® 2

\* Does not include vehicle mount (approx. 60 lbs - 184 lbs for straight blades). Please refer to the eMatch program for specific vehicle applications. \*\* Blade height shown is for the 55° attack angle. The 65° attack angle blade height is 28.5" and the 75° attack angle blade height is 27.0".