



## **SPEED-CASTER(TM) 525 & 900 Specifications**

<b>Imperial</b>	<b>SPEED-CASTER 525</b>	<b>SPEED-CASTER 900</b>
Capacity	5.25 cu ft	9.00 cu ft
Hopper Construction	Polyethylene	Polyethylene
Dimensions Overall (LxWxH)	20 ½" x 38" x 34"	24" x 52" x 36"
Approx. Weight (Empty)	160 lb	180 lb
Motor	Dual Electric, 12V 1/3 HP	Dual Electric, 12V 1/3 HP
Auger (Diam. x Length)	3" x 14" Heavy-Duty Solid Steel	3" x 20" Heavy-Duty Solid Steel
Spinner Size	10"	12"
Spreading Width	Up to 30'	Up to 40'
Materials	Bagged Rock Salt	Bagged Rock Salt
Vehicle Application	Tractors, UTVs, SUVs, 1-Ton or Smaller Pickups	Tractors, 1-Ton or Smaller Pickups
Available Mounts	Standard 2" Receiver, 3-Point Combo Mount	Pivot Mount, 2" Receiver Mount (Requires Adapter Mount), 3-Point Hitch Mount*

<b>Metric</b>	<b>SPEED-CASTER 525</b>	<b>SPEED-CASTER 900</b>
Capacity	0.15 cu m	0.25 cu m
Hopper Construction	Polyethylene	Polyethylene
Dimensions Overall (LxWxH)	52.10 cm x 96.50 cm x 86.40 cm	60.90 cm x 132.10 cm x 91.40 cm
Approx. Weight (Empty)	72.6 kg	81.7 kg
Motor	Dual Electric, 12V 1/3 HP	Dual Electric, 12V 1/3 HP
Auger (Diam. x Length)	7.62 cm x 35.56 cm Heavy-Duty Solid Steel	7.62 cm x 50.80 cm Heavy-Duty Solid Steel
Spinner Size	25.40 cm	30.50 cm
Spreading Width	Up to 9.14 m	Up to 12.19 m
Materials	Bagged Rock Salt	Bagged Rock Salt
Vehicle Application	Tractors, UTVs, SUVs, 1-Ton or Smaller Pickups	Tractors, 1-Ton or Smaller Pickups
Available Mounts	Standard 2" Receiver, 3-Point Combo Mount	Pivot Mount, 2" Receiver Mount (Requires Adapter Mount), 3-Point Hitch Mount*

\*Mounts sold separately