

ALL-NEW

**STORM
BOXX™**

WITH TRACE™ EDGE TECHNOLOGY



GET A STEP AHEAD OF WINTER

When large storms are on the horizon, you want to attack it with all that you have. With TRACE edge technology, the all-new STORM BOXX™ pusher plows move massive amounts of snow—scraping down to the pavement—to reduce the amount of salt needed. Available in 8', 10', 12', 14', and 16' widths, these pushers blaze new trails.

FISHERPLOW.COM

STORM BOXX™ WITH TRACE™ EDGE TECHNOLOGY

PUSHER PLOW

The all-new STORM BOXX line up of pusher plows come in 8', 10', 12', 14', and 16' widths. A common carrier attachment system with a floating coupler allows compatibility with skid loaders, wheel loaders, tractors, and backhoe loaders. The patent-pending TRACE edge technology allows the cutting edge to contour to the plowable surface for maximum snow removal. The FISHER® dealer network is available for best-in-class service and support.



TRACE EDGE TECHNOLOGY

The terrain-response advanced cutting edge is comprised of independent, 2' sections that raise, oscillate, and trip to accommodate contours and obstacles in the plowable surface. Working together, the sections remove more snow, reducing the amount of salt required. Two greasing locations allow the operator to keep the components well lubricated for maximum performance.



RAISE



OSCILLATE



TRIP

SELF-LEVELING SIDE PLATES WITH HEAVY-DUTY SHOES

The side plates with heavy-duty shoes self-level to ensure the TRACE edge technology remains in direct contact with the plowable surface. The shoes are built to be easily replaceable to extend the life of the pusher.

3/4" CUTTING EDGE WITH CARBIDE INSERTS

The STORM BOXX plow performs in the most grueling commercial conditions. Each 2' section comes standard with a 3/4" cutting edge with carbide insert. Each section uses the same cutting edge for easy replacement when necessary so you can replace only the sections that show wear.

COMMON ATTACHMENT PLATE

A common attachment plate and floating coupler makes installation easy with a wide variety of equipment and machinery, including skid-steers, wheel loaders, backhoes, and tractors. The floating coupler reduces negative down pressure from the vehicle, protecting against premature wear of the pusher cutting edge and components.



EASY OPERATION

Operation of the STORM BOXX plow is conveniently tied into the equipment's controls. Simply raise and lower the lift arm and angle the attachment plate to position the pusher in the correct orientation.




SPECIFICATIONS

DIMENSIONS					OPERATION				CONSTRUCTION				
Blade Width	Blade Height	Side Plate Width	Side Plate Height	Moldboard Radius	Cutting Edge Technology	Cutting Edge Material	Approx. Snow Capacity	Approx. Weight*	Mount Type	Machine Application	Vehicle HP Compatibility	Wheel Loader HP Compatibility	Tractor HP Compatibility
8' (2.44 m)	30" (76.2 cm)	56" (142.24 cm)	30" (76.2 cm)	27" (68.58 cm)	TRACE — Terrain Response Advanced Cutting Edge	High-carbon steel with carbide inserts	75 cu ft (2.14 cu m)	2127 lb (964.63 kg)	Skid-Steer	Skid-Steer	30-50 hp	—	—
10' (3.05 m)	30" (76.2 cm)	56" (142.24 cm)	30" (76.2 cm)	27" (68.58 cm)			94 cu ft (2.68 cu m)	2249 lb (1019.95 kg)	Skid-Steer	Skid-Steer	30-50 hp	—	—
8' (2.44 m)	36" (91.44 cm)	56" (142.24 cm)	36" (91.44 cm)	27" (68.58 cm)			108 cu ft (3.06 cu m)	2221 lb (1007.26 kg)	Skid-Steer / Coupler	Skid-Steer / Tractor / Wheel Loader	—	50-75 hp	50-100 hp
10' (3.05 m)	36" (91.44 cm)	56" (142.24 cm)	36" (91.44 cm)	27" (68.58 cm)			135 cu ft (3.82 cu m)	2377 lb (1078.00 kg)	Skid-Steer / Coupler	Skid-Steer / Tractor / Wheel Loader	—	50-75 hp	50-100 hp
12' (3.66 m)	42" (106.68 cm)	56" (142.24 cm)	42" (106.68 cm)	46" (68.58 cm)			219 cu ft (6.19 cu m)	2644 lb (1199.09 kg)	Coupler	Wheel Loader	—	100-125 hp	75-150 hp
14' (4.27 m)	42" (106.68 cm)	56" (142.24 cm)	42" (106.68 cm)	46" (68.58 cm)			TBD	2907 lb (1318.37 kg)	Coupler	Wheel Loader	—	100-125 hp	75-150 hp
16' (4.88 m)	42" (106.68 cm)	56" (142.24 cm)	42" (106.68 cm)	46" (68.58 cm)			TBD	3170 lb (1437.64 kg)	Coupler	Wheel Loader	—	100-125 hp	75-150 hp

*Approximate weight is less mount



Fisher Engineering | 50 Gordon Drive | Rockland, Maine 04841

fisherplows.com |   

Fisher Engineering reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used. Fisher Engineering or the vehicle manufacturer may require or recommend optional equipment for snow removal. Do not exceed vehicle weight ratings with a snowplow. Fisher Engineering offers a limited warranty on all snowplows and accessories. See separately printed page for this important information. The following are registered (®) or unregistered (™) trademarks of Douglas Dynamics, LLC: FISHER®, STORM BOXX®, TRACE™

